

Pedestal Adhesive

PRODUCT INFORMATION AND APPLICATION GUIDE

Panelway Pedestal Adhesive is used to bond raised access floor pedestal base plates to indoor concrete subfloors. The photographs below show the packaging and an example of a bonded pedestal base.

Product details

Property	Specification
Nominal pack volume	1 L
Shelf life	12 months
Recommended trowel notch spacing	Approximately 10 mm
Recommended trowel notch depth	1-1.5 mm

How to apply

- 1 Prepare the surfaces** Ensure the subfloor and bonding surfaces are clean, dry and free of loose dust.
- 2 Apply the adhesive** Use a spatula, notched trowel or brush to coat the full bonding surface of the pedestal base plate.
- 3 Position and press** Place the base plate onto the subfloor. Move it slightly and press gently to achieve contact.
- 4 Protect the bond** Do not expose the adhesive to water before it has dried.

Packaging and application



Sealed container | Open container | Bonded pedestal base

Storage and handling

Keep tightly sealed and store in a cool place. If the adhesive is too thick, methanol or anhydrous ethanol may be used for dilution as specified in the product instructions. Consult the applicable Safety Data Sheets before handling the adhesive or dilution solvents.

The nominal pack volume is taken from the product label. Container photographs are for illustration.

Panelway (China) Ltd.

International Marketing & Sales

Suite No. 532B, 5/F, Star House
3 Salisbury Road, Tsim Sha Tsui
Kowloon, Hong Kong

Manufacturing Base · Shandong, China
International Sales & Support · Hong Kong

Mr. Nie / General Manager

Mobile / WhatsApp

+86 185 0081 8227

nie@panelwayaccessfloors.com

www.panelwayaccessfloors.com